



Narrow Aisle and Very Narrow Aisle Truck Selector Guide

Model	Capacity		Power Source	Triple Mast Lift Height Available		Quad Mast Lift Height Available		Storage aisle with 48" l x 40" w load (1.2M l x 1M w load)	
	lbs.	kg.		in.	M	in.	M	in.	M
<i>Bendi</i>									
Bendi B3/25	2500	1136	Electric	283	7.19	N/A	N/A	71	1.80
Bendi B3/35	3500	1591	Electric	283	7.19	N/A	N/A	71	1.80
Bendi B30	3000	1364	Electric	272	6.91	312	7.92	78	1.98
Bendi B40	4000	1818	Electric	360	9.14	312	7.92	78	1.98
Bendi B45	4500	2046	Electric	360	9.14	312	7.92	84	2.13
B45HL	4000	1818	Electric	433	11.00	N/A	N/A	84	2.13
B40IC	4000	1818	LP Gas	216	5.49	276	7.01	78	1.98
<i>Drexel SwingMast</i>									
SLT-30	3000	1364	Electric	269	6.83	268	6.81	56	1.42
SLT-35	3500	1591	Electric	269	6.83	276	7.01	56	1.42
SLT-35-HLC	3500	1591	Electric	302	7.67	N/A	N/A	66	1.68
SL-30	3000	1364	Electric	272	6.91	312	7.92	60	1.52
SL-40	4000	1818	Electric	360	9.14	312	7.92	60	1.52
SL-66	6000	2727	Electric	360	9.14	294	7.47	66	1.68
SL-88	8000	3636	Electric	360	9.14	N/A	N/A	72	1.83
SL-120	12000	5455	Electric	243	6.17	N/A	N/A	78	1.98
R-40-SL	4000	1818	LP Gas/Diesel	240	6.01	N/A	N/A	66	1.68
R-60-SL	6000	2727	LP Gas/Diesel	240	6.01	N/A	N/A	72	1.83
<i>Drexel EX</i>									
FL-40-EX	4000	1818	Electric	236	5.99	N/A	N/A	144	3.66
FL-60-EX	6000	2727	Electric	234	5.94	N/A	N/A	144	3.66



B30



SL40



B40IC



B3